Material Safety Data Sheet

ACID MagicTM Muriatic Acid Replacement

Product Numbers: USA/32, USA/128, USA/5G, USA/15G, USA/30G, USA/55G, USA/275G, USA/330G

ISSUE DATE: April 2006 (Supersedes November 2005)



6120 E. 58th Avenue Commerce City, CO 80022 Ph: (303) 799-9401 Toll Free: 1-800-843-3343 Fax: (303) 799-9408 24-Hour Emergency Telephone INFOTRAC: 1-800-535-5053 *www.certol.com*

Certol International, LLC urges each customer or recipient of this MSDS to study it carefully to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation toxicology and fire prevention, as necessary or appropriate, to use and understand the data in this MSDS.

To promote safe handling, each customer or recipient should: (1) notify its employees, agents, contractors, and others whom it knows or believes will use this material of the information regarding hazards or safety; (2) furnish this information to each of its customers for the product; and (3) request its customers to notify their employees, customers, and other users of the product of this information.

Emergency and First Aid Procedures

Swallowing: Rinse mouth and throat thoroughly with tap water. Drink large amounts of water. DO NOT induce vomiting. Do not give anything by mouth to an unconscious or convulsing person. Seek medical attention immediately.

Skin Contact: Wash skin with mild soap and water. Seek medical attention if irritation persists.

1. Identification

<u>Product Name:</u> ACID Magic™ Muriatic Acid Replacement <u>Chemical Name:</u> N/A <u>Formula:</u> Blend. <u>Synonyms:</u> N/A

2. Hazardous Ingredients

PRINCIPAL HAZARDOUS COMPONENTS	CAS #	
Hydrochloric Acid	7647-01-0	

3. Physical Data

Appearance: Clear to slightly yellow liquid. Odor: Slightly pungent. Solubility In Water by wt.: Complete. Boiling Point: Approximately 212°F (100°C) Freezing Point: -4°F (-20°C) Vapor Density: (Air = 1) 3 max. Evaporation Rate (n-Butyl Acetate = 1): < 1 Specific Gravity: 1.11 @ 68°F (20°C) pH: Less than 1 @ 68°F (20°C)

4. Fire And Explosion Hazard

<u>Flash Point:</u> Not flammable. <u>Flammable Limits In Air:</u> N/A <u>Special Fire Fighting Procedures:</u> Wear self-contained breathing apparatus and protective equipment. **Inhalation:** Remove the affected victim from exposure. Administer artificial respiration if breathing stopped. Seek medical attention immediately.

Eye Contact: Flush eyes with water for 15 minutes. Seek medical attention if irritation continues.

> <u>Unusual Fire And Explosion Hazards</u>: Product is corrosive and produces hydrogen chloride fumes when heated. May react with many metals liberating hydrogen gas, which can form explosive mixtures.

5. Health Hazard Data

COMPONENT	OSHA/ PEL	ACGIH/ TLV	Others (optional)
Hydrochloric Acid	5 ppm	5 ppm	N/A

Effect Of Overexposure:

<u>Swallowing:</u> May be fatal if large amounts are ingested. May cause severe burns to mouth, throat, and gastrointestinal tract. Skin Absorption: Overexposure will irritate or burn

<u>Skin Absorption:</u> Overexposure will irritate or burn respiratory tract.

Inhalation: Overexposure will irritate or burn respiratory tract.

Eye Contact: Corrosive. May cause redness, pain, burns, and irreversible damage to eye.

Carcinogenicity:

NTR: No IARC: No OSHA: No

6. Reactivity Data

Stability: Stable.

Conditions To Avoid: Avoid exposure or contact to extreme temperatures and incompatible chemicals. Incompatibility (Materials To Avoid): Most metals, alkalis, strong oxidants, acetic anhydrides, oleum, amines, and vinyl

Active and the second and the second and the second active and the second active and the second active and the second active act

gas evolved from heating; hydrogen gas evolved by reaction to metals.

Hazardous Polymerization: Will not occur.

7. Spill, Leak, And Waste Disposal Procedures

Steps To Be Taken In Case Material Is Released Or Spilled: Deny access to the area. Vacuum up as much as possible. Absorb residue with absorbent. Flush surface with water and neutralize with soda ash or other acidneutralizing agent. Prevent material from entering waterways. Reportable quantity (RQ) is 8,000 lbs. Waste Disposal Method: Dispose according to all local, state, and federal regulations.

8. Handling And Storage

Store in dry, well-ventilated area away from heat and direct sunlight. Do not store near alkalis, highly flammable or oxidizing substances. Store in closed, properly labeled, acid resistant container. Product must not contact hydrogen sulfide gas, chlorine bleach, or cyanide. Keep out of reach of children.

9. Special Protection Information

<u>Respiratory Protection:</u> For concentrates above the PEL limit, use an acid canister gas mask up to 2%. For higher concentrations, use an air line mask or self-contained breathing apparatus. Note: The limit is less likely to be reached because of the reduced fuming, compared to conventional hydrochloric acid.

<u>Ventilation</u>: Use in well-ventilated area to eliminate vapors. Mechanical exhaust is not normally required unless used in confined area and/or individual has sensitive respiratory system.

<u>Protective Gloves:</u> Neoprene or VBR recommended. <u>Eye Protection:</u> Use safety goggles and/or face shield. <u>Protective Clothing:</u> Where contact may occur, wear protective clothing and/or chemical resistant apron. <u>Other Protective Clothing Or Equipment:</u> An eyewash station should be nearby and ready for use.

10. Regulation Information


<u>Status On Substance Lists:</u> N/A <u>Federal EPA:</u> N/A <u>Status Right-To-Know:</u> N/A

11. Transportation Data

D.O.T.: Quarts and gallons = ORM-D Consumer Commodity. Bulk quantities = Corrosive.

CHEMICAL WARNING LABELS

Required on containers, tubs, and bottles, which are filled from original containers with potentially hazardous substances.



The information contained herein is furnished without warranty or legal responsibility of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and safety and health of employers.